ADM

Advanced Display Materials, Inc. 12750 Center Court Drive. Suite 240 Cerritos, CA 90703 Tel #: 562-809-7300 Fax #: 562-809-7322

Specifications Sheet

Item: ADM P.I.T. (Photo Image Textile - Opaque Grade)

	-			January 16th, 2017
CATEGORY		UNIT	RESULT	TEST METHOD
Surface Finish			Matte	
Thickness	Polyester		(200+2)	KSA1107
	Adhesive	μm	(30+2)	KSA1107
Adhesion	After 20 min.	kgf/in	(0.42+0.01)	KSA1107
	After 24 hr.	kgf/in	(0.74+.002)	KSA1107
Ball Tack	L	Ball No.	10	KSA1107
Residue		_	No	30°C/90%/18hr/Weight 1KG
		—	No	35°C/90%/18hr/Weight 0.5KG
		_	No	65℃/18hr/Weight 1KG
Tensile Strength	L	kgf/mm²	(≥1.16)	ASTM D882
	W	kgf/mm²	(≥1.00)	ASTM D882
Elongation	L	%	(≤100)	ASTM D882
	W	%	(≤80)	ASTM D882
Care Note	With no impact, scratch and humidity			
Width		cm	Up to 152	
Shelf Life		About 1 year		
Weight		342 g per SQ.M		
Standard Roll Length		m	30	

* This information is to the best of the company's knowledge and believed accurate and reliable as of the date indicated.

However, no representation, warranty or guarantee of any kind, express or implied, is made as to its accuracy, reliability or completeness

and we assume no responsbility for any loss, damage or expense, direct or consequential, arising out of use.

It is the user's responsibility to satisfy himself as to the suitableness and completeness of such information for his own particular use.